

Fiche Technique

Model	1000VA
Capacity	1000VA/600W
Materials	Plastic
INPUT	
Voltage	220/230/240 VAC
Voltage Range	145-295 VAC
Frequency Range	60/50 Hz (Auto sensing)
OUTPUT Voltage	220/230/240 VAC
AC Voltage Ragulation (Bat Mode)	±10%
Frequency Range (Bat Mode)	60Hz or 50Hz ± 1Hz
Transfer time	Typical 2-6ms
Waveform (Bat Mode)	Simulated Sinewave
Power factor	0.6
Battery	
Battery Type&Number	12V 9Ah*1
Floating Charging Voltage	13.7VDC
Charging ability	4-6 hours recover to 90% capacity
Protection	
Full protection	Overload,discharge,and overcharger protection
Led Indications	
Line mode	Green lighting
Battery mode	Flashing every 4 seconds
Charging	
Fault	Green lighting
Sound Alarm	
Battery mode	Sound every 4 seconds
Low battery	Sound every 1 second
Fault	keep sounding
Dimension,D*W*H(mm)	280x100x140
Net Weight (kgs)	4.9
Environment	
Humidity	0-90% Relative Humidity 0-40 °C (Non-condending)
Noisy Level	Less than 40dB

Service Commercial

Mobile : 0560 989 902 - 0560 989 903 - 0560 989 904

Fixe : 023 804 346 - 023 804 348 - 023 804 349

Coop El Asel Lot 434 N° 01

Lido, Mohammadia, Alger

© 2018 MMC TECHNOLOGIE