

Fiche Technique

MODEL	1KVA
Specification	Single Phase In & Out
Capacity	1KVA/800W
Rated voltage	220VAC
Input voltage range	115-300VAC \pm 5
Input frequency range	(45-55) \pm 0.5Hz
bypass voltage	80VAC \times (1 \pm 5%)-285VAC \times (1 \pm 5%)
battery group voltage	24V
battery method	Internal battery 7ah x 2pcs
backup time(half/full)	half load \geq 10 minutes, full load \geq 5minutes(standard)
maximum input current when power on	<150% of rated current
battery charging time	5hours can charge to 90%(standard)
Output voltage	220VAC \pm 1%(invert output)
Output frequency	50 \pm 5Hz(when AC input is normal) 50Hz \pm 1% (when ac inout is abnormal)
wave form	sine wave THD<3%(linear load) sine waveTHD<8%(Nonlinear load)
output power factor	0.8
Overload ability	130% load lasting not less than 30s,Recovery point is 90% load
Output current peak coefficient	0.125694444
Transfer time between AC and Battery	0ms
Communication and monitoring functions	RS232(can transfer to 485, Dry node Smart slot(can expand to SNMP,SMS and other monitoring methods)
N.W(KG)	8.5
G.W(KG)	9
Unit Size(W X H X D)mm	365*145*215
Carton Size(W X H X D)mm	475*465*340

Service Commercial

Mobile : 0560 989 902 - 0560 989 903 - 0560 989 904

Fixe : 023 804 346 - 023 804 348 - 023 804 349

Coop El Asel Lot 434 N° 01

Lido, Mohammadia, Alger

© 2018 MMC TECHNOLOGIE