

## Fiche Technique

Model	2000VA
Capacity	2000VA/1200W
Materials	Metal
<b>INPUT</b>	
Voltage	220/230/240 VAC
Voltage Range	145-295 VAC
Frequency Range	60/50 Hz (Auto sensing)
<b>OUTPUT Voltage</b>	220/230/240 VAC
AC Voltage Regulation (Bat Mode)	±10%
Frequency Range (Bat Mode)	60Hz or 50Hz ± 1Hz
Transfer time	Typical 2-6ms
Waveform (Bat Mode)	Simulated Sinewave
Power factor	0.6
<b>Battery</b>	
Battery Type&Number	12V 9Ah*2
Floating Charging Voltage	27.4VDC
Charging ability	4-6 hours recover to 90% capacity
<b>Protection</b>	
Full protection	Overload, discharge, and overcharger protection
<b>Led Indications</b>	
Line mode	Green Lighting
Battery mode	Red lighting
Charging	Yellow lighting
Fault	Red lighting
<b>Sound Alarm</b>	
Battery mode	Sounding every 4 seconds
Low battery	Sounding every 1 second
Fault	keep sounding
Dimension, D*W*H(mm)	380x123x193
Net Weight (kgs)	12.5
<b>Environment</b>	
Humidity	0-90% Relative Humidity 0-40 °C (Non-condensing)
Noisy Level	Less than 40dB

### Service Commercial

Mobile : 0560 989 902 - 0560 989 903 - 0560 989 904

Fixe : 023 804 346 - 023 804 348 - 023 804 349

*Coop El Asel Lot 434 N° 01*

*Lido, Mohammadia, Alger*

© 2018 MMC TECHNOLOGIE